

Decals, Stickers,

Jewel Kits

JD1	55/56 Jacking instruction	1.00
JD2	57 Jacking instruction	1.00
DP557	55,56. early 57 data plate	1.10
DP57L	Late 57 data plate	1.10
AT556	Auto trans. (glove box)	1.00
HD1	Heater instructions	1.00
TP556	55/56 Engine oil/tire pressure (glove box)	1.00
TP57	57 Engine oil/Tire pressure (glove box)	1.00
DL56	Door latch	1.30
TDF93	Lifeguard design (door jam)	1.55
TDF229	Engine Foundry Tag	1.10
AC556	55/56 Air cleaner	2.00
AC57	57 Air cleaner	1.10
CL567	56/57 Coil	1.10
OF557	Oil filter element type	2.20
GP1	55 Generator plate w/rivets	3.95
GN56	56 Generator	1.10
GN57	57 Generator	1.10
VR55	55 Voltage, regulator	1.10
VR567	56 Voltage, regulator silver	1.10
VR57	57 Voltage, regulator yellow	1.10
SP1	55 Starter plate w/rivets	3.95
ST567	56/57 Starter	1.10
AS557	Hood block off plate	1.00
FT557	Soft top (glove box)	1.00
18B	56 Radio tube location	1.00
18C	57 Radio tube location (2) decals	2.00
TJK55	55/56 Jewel kit	5.15
TJK57	57 Jewel kit	7.20
TJK57E	57 Jewel kit early	7.20
16A	55 Inspection stamp decal set	9.95
16B	56 Inspection stamp decal set	9.95
16C	57 Inspection stamp decal set	9.95
TDF72	Valve cover 292, pr	7.10
TDF71	Valvecover 312, pr	7.10
CDS55	55 Decal kit	16.50
CDS56	56 Decal kit	16.50
CDS57	57 Decal kit	15.50

SERVICE INSTRUCTIONS

CLEAN AND REFILL OIL BASE WITH ONE PINT OF NEW OIL EACH TIME CRANKCASE IS DRAINED WASH UPPER FILTER IN KEROSENE AND DRAIN. USE S.A.E. 30 OIL FOR TEMPERATURES ABOVE FREEZING S.A.E. 10 BELOW FREEZING. CLEAN MORE FREQUENTLY UNDER EXTREME DUSTY CONDITIONS. PATS. NOS. 248745, 2557236, 2557237 OTHER PATS. PENDING. MADE IN U.S.A.

USE GENUINE
Ford
REPLACEMENT PARTS FOR SERVICE INSTRUCTIONS SEE OWNERS MANUAL

AC57

USE ONLY AUTOMATIC TRANSMISSION FLUID TYPE A
CHECK TRANSMISSION FLUID LEVEL FREQUENTLY. MAKE SURE TO USE AUTOMATIC TRANSMISSION FLUID AT NORMAL OPERATING TEMPERATURES AND ENGINE ON TO OIL LEVEL WITH SEVERAL FEET OF INCH POSITION.

AT556

FAC-12029-A
12 VOLTS *Ford* 7113
USE WITH EXTERNAL RESISTOR

CL567

SERIAL NO.
THIS VEHICLE IS CONSTRUCTED UNDER UNITED STATES LETTERS PATENT
2 137 729 2 310 416 2 617 681 2 631 694
2 185 083 2 390 719 2 627 896 2 634 148
2 270 127 2 617 879 2 528 833 2 639 938
OTHER PATENTS PENDING
BODY COLOR TRIM PRODUCTION CODE

MADE IN U.S.A. BY *Ford* REG. U.S. PATENT OFFICE

DP557

SERIAL NUMBER MADE IN *Ford* REG. U.S. PAT. OFF.
BODY COLOR TRIM DATE TRANS AXLE
THIS VEHICLE IS CONSTRUCTED UNDER UNITED STATES LETTER PATENTS
2 270 122 2 390 719 2 628 833 2 677 372 2 708 396
2 390 937 2 617 829 2 631 696 2 627 376 2 726 894
2 370 416 2 617 681 2 639 938 2 608 013
OTHER PATENTS PENDING

DP57L

ENGINE OIL
NOT LOWER THAN 12" IN S.A.E. 20 or 20W DOWN TO MINUS 10" IN S.A.E. 10W BELOW MINUS 10" IN S.A.E. 5W
TIRE PRESSURE
TIRE SIZE FRONT REAR
7.50 X 14 4PLY 22 22

and when service is needed specify Genuine Ford Parts

TP57

FBA 10000-C GENERATOR
11 VOLTS *Ford* 40 AMPS

GP1

FBY-10000-B GENERATOR
15V 30A *Ford* NEG GRD

GN56

INSTRUCTIONS FOR REMOVING BLOWER & DUCT ASSY

DISCONNECT THE BLOWER WIRES FROM HARNESS & GROUND
TO INSTALL REVERSE & FUSE ASSEMBLY REVERSE ABOVE PROCEDURE

HD1

REMOVE COVER FOR SUMMER OPERATION

AS557

FAR-11001-A STARTING MOTOR
12 VOLTS *Ford* MADE IN U.S.A.

ST567

FOR INSTRUCTIONS FOR OPERATION AND CARE OF FOLDING TOP, SEE OWNERS MANUAL

FT557

JACKING INSTRUCTIONS

- Set Emergency Brake and put car in Reverse (or with Forward) set Spring Brakes on Park (or Hand).
- Place Jack Hook on Jacking Eye (Location appears in every 15" to 20" from center of bumper).
- Lower Bumper Jack Body with Jack Column in vertical position as shown in illustration.
- When jacking rear of car, block front wheels to prevent car from rolling.

JACK STORAGE

- Place Jack Block over Jack.
- Slide upper end of Column Assembly and Top 6" Sliding Jaws end of Column Jack Base Socket.
- Insert Metal Hook of Child-Proof Strap (C) into Slot of Lip (A).
- Slide Rubber Loop of Third-Block Strap over End Hook on Jack and in front Jack Wheel (see Top View) tighten lock on Jack Hook.
- Slide Wheel Wrench under Spare Tire.
- Wedge Jack Block between Spare Tire and Wheel Well.

NOTE: Lubricate Jack Mechanism on Last Time Every 3 Months.

JD1
JD2

FAD-10505-A
7 VOLTS *Ford* 40 AMPS

VR55

FAP-10505-B REGULATOR
15V 30A *Ford* NEG GRD

VR567

OIL *Ford* FILTER
SEE OPERATORS MANUAL FOR REPLACEMENT INSTRUCTIONS USE GENUINE REPLACEMENT CARTRIDGE

Thunderbird TDF72

TDF71
THUNDERBIRD Special

12 VOLT MAR 23 1956

Ford PAINT OK 232
Ford GLASS OK 332
Ford TRIM OK 532
Ford FINAL OK 259
TESTED ROAD 512
TESTED ROAD 512
16A 16B 16C

TJK55 OF557
GEN OIL
TJK57